Elk River TMDL Development Update and Overview of the Draft Upper Elk River Sediment Source Analysis

June 28, 2011 Eureka, CA

Adona White, PE Basin Planning Unit



Meeting Agenda

- Introductions
- Staff Presentation 6:15-6:45
- Questions 6:45-7:00
- Break 7:00-7:15
- Discussion 7:15-7:45
- Wrap-up 7:45-8:00


Presentation Overview

- Background on Regional Water Board Efforts in Elk River
- Geographic Scope of TMDL Analysis and Implementation Strategy
- Watershed Overview (Ch1)
- Impairment Overview (Ch2)
- Upper Elk River Source Analysis (Ch3)
- Next steps



Elk River Watershed: 58.3 mi²

North Fork Elk River (22.5mi²) South Fork Elk River (19.5 mi²) Lower Elk River (10.4 mi²) Martin Slough (5.9 mi²)



Data Availability

- Upper Elk River Forested Lands
 - Hillslope sediment source and instream data
 - Pursuant to Regional Water Board requirements
 - Ownership-management plan requirements
 - Grant-funded projects
- Lower Elk River and Martin Slough
 - Lack of hillslope and instream data

CEQA Scoping Comments

- Avoid the generalizations; rely on sitespecific data.
- Upper and Lower Elk are very different; inappropriate to apply generalizations from upper watershed to lower watershed

Geographic Scope

- Upper Elk River
 - TMDL technical analyses(Source analysis and load allocations)
 - Implementation to reflect technical analyses;
 address instream sediment deposits
- Lower Elk River and Martin Slough
 - Assessing options to address sediment impairments
 - Reliance on existing regulatory programs

Elk River TMDL Draft Staff Report

- Ch 1: Introduction May 2009
- Ch2: Problem Statement May 2009
- Implementation Framework May 2009
- CEQA Scoping May 2009; Staff and Board workshops October/November 2009
- Ch 3: Upper Elk River Sediment Source Analysis – May 2011

www.waterboards.ca.gov/northcoast/water_issues /programs/tmdls/elk_river/

Chapter 1: Background

- Mid-1990's: Severe sedimentation documented from upper watershed
- Regional Water Board sediment control efforts begin
- 1998: Elk added to impaired waters list
- TMDL Development:
 - Technical Analyses
 - Implementation Program

Chapter 2: Problem Statement:

Beneficial Use Impairment & Exceedence of Water Quality Objectives

- Sediment deposition
 - Reduced channel capacity; altered morphology
 - Nuisance flooding conditions
 - Pool filling; spawning habitat
- Elevated suspended sediment concentrations and turbidity levels
 - Limit fish feeding and survivability
 - Limit water supplies; increased maintenance

Upper Elk River Source Analysis

- Timing and magnitude of natural and managementrelated <u>hillslope</u> sediment sources
- Sub-basin analyses based on site specific data
- Reference and managed study sub-basins for generalized loadings where no site specific data available
- Time periods analyzed: 1955-1966, 1967-1974, 1975-1987, 1988-1997, 1998-2000, and 2001-2003.
 - Recent time period pending updated landslide inventories
 - Hillslope loads could be compared with SS loads

Upper Elk River Source Analysis Data sources:

- Humboldt Redwood Company
- Pacific Lumber Company
- Green Diamond Resource Company
- Bureau of Land Management
- Pacific Watershed Associates

- Stillwater Sciences
- North Coast Regional Water Board
- Redwood Sciences Laboratory
- California Geologic Survey
- Salmon Forever
- Humboldt State University


Upper Elk River Source Analysis Approach

- TMDL Drainage Network
 - Field-surveys of study sub-basins
 - Identified natural and managed drainage area thresholds for channel initiation.
 - Calculated natural and managed drainage network for analysis time periods.

Source Analysis: Natural

	Sediment Source	Data Sources Relied Upon / Approach		
Natural	Soil Creep	Literature		
	Bank Erosion	Field surveys; natural drainage density estimate		
	Small Streambank Landslides	Field surveys; natural drainage density estimate		
	Shallow Hillslope Landslides	Aeas not harvested in past 15 years		
	Deep seated Landslides	CGS mapped active features; Palco WA rates		

Natural Sources Summary




Source Analysis: Management

	Sediment Source	Data Sources Relied Upon / Approach		
Management	Low Order Channel Incision	Field-based estimates of managed and natural drainage density; assumed 75% occurred in 1950's and 5% in each subsequent decade		
	Management- Related Soil Creep	Soil creep to management-induce channel network		
	Management- Related Bank Erosion	Field surveys in managed study sub-basins; managed drainage density estimate; subtracted natural loading		
	Management- Related Open Slope Shallow Landslides	Sub-basin specific landslide inventory data from Palco WA and 2005 ROWD; non-road-related slides, includes some skid-related slides		
	Road-related Landslides	Sub-basin specific landslide inventory data from Palco WA and 2005 ROWD		

Source Analysis: Management

	Sediment Source	Data Sources Relied Upon / Approach		
Management	Management- Related Streamside Landslides	Field surveys in managed sub-basins in Freshwater Creek; applied to natural drainage density estimate assuming bank erosion captured features in management-induced network; subtracted natural loading		
	Management- Related Discharge Sites	Sub-basin specific site inventories from Palco WA, HRC CAO reports, GDRC WDR reports, BLM reports		
	Post-Treatment Discharge Sites	Compiled monitoring results from BLM, HRC, and GDRC from sites treated in Elk River.		
	Skid Trails	Compiled findings from Elk River skid-related inventories on BLM and HRC lands to estimate loading from skid sties not included in Management Discharge Site inventories		
	Road surface erosion	Sub-basin road densities & surface condition based on Palco WA and ROWD; unit loading based upon Palco ROWD		
	Harvest surface erosion	Estimated harvest history in clear-cut equivalents based upon CDF, Palco WA, and Palco ROWD; unit loading based upon Palco WA		

Management Sources Summary



Comparison with Palco Watershed Analysis

	TMDL	Palco WA		
	Source Category	1988-2000 (yd³/mi²/yr)	Source Category	1988-2000 (yd³/mi²/yr)
	Soil Creep	0.44	Soil Creep	52
I _	Bank Erosion	9	Bank Erosion	38
l la	Shallow Landslides	26	Shallow Landslides	68
Natura	Streamside Landslides	30	Streamside Landslides	276
~	Deep Seated Landslides	0	Deep Seated Landslides	3
	Natural Total	66	Natural Total	437
	Low Order Channel Headward Incision	24		
	Soil Creep	1		
Management	Bank Erosion	52	Bank Erosion	38
	Streamside Landslides	272	Road-related Streamside Landslides	162
	Open-slope Shallow Landslides	182	Open-slope Shallow Landslides	144
	Road-related Shallow Landslides	237	Road-related Shallow Landslides	168
Σ	Discharge sites	59	Gullies	28
	Skid Trails	15		
70	Post-Treatment Discharge Sites	3		
	Road surface erosion	118	Road surface erosion	32
	Harvest Surface Erosion	5	Surface Erosion	6
	Management Total	967	Management Total	579
24	Total Loading	1,033	Total Loading	1,016
	Percent over Natural Loading	1,576%	Percent over Natural Loading	232%

Next Steps: Upper Elk River

- Public Comment
- Revise Chapters 1-3
- Targets
- Linkage
- Load Allocations
- Implementation Program
- Board Workshop and direction

For further information, and to download TMDL documents for review and comment:

http://www.waterboards.ca.gov/northcoast/ progams/tmdl/elk

Adona White: Elk River TMDL Development

707-576-2672 AWhite@waterboards.ca.gov

Holly Lundborg: Basin Planning Senior

707-576-2609 HLundborg@waterboards.ca.gov

Matt St. John: Acting Non-point Source Division Chief

707-570-3762, MStJohn@waterboards.ca.gov